

## Material Safety Data Sheet

### SECTION 1 IDENTIFICATION

**Product Name:** GOLDEN SPECTRO® Total Tac™ Chain Lube

**Manufacturer:**  
**Intercontinental Lubricants Corp./**  
**Spectro Oils of America**  
993 Federal Road  
Brookfield, CT 06804  
(203) 775-1291 Fax: (203) 775-8720

MSDS Date of Preparation: 8/24/98

### SECTION 2 PRODUCT COMPONENTS

| INGREDIENTS     | CAS#.     | WT.%  | EXPOSURE LIMITS                                       |
|-----------------|-----------|-------|---|
| n-Hexane        | 110-54-3  | 30-40 | 50 ppm TWA (ACGIH)<br>500 ppm TWA (OSHA)              |
| Carbon Dioxide  | 124-38-9  | 1-5   | 5,000 ppm TWA (OSHA/ACGIH)<br>30,000 ppm STEL (ACGIH) |
| Polyisobutylene | 9003-29-6 | 50-70 | None Established                                      |

### SECTION 3: HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

This product is a clear, colorless liquid with a petroleum odor. Flammable aerosol (Flash Point 15°F). May cause eye and skin irritation. May be absorbed through the skin in harmful amounts. Breathing vapors may cause respiratory irritation and central nervous system effects including headache, dizziness, nausea, confusion and coma. Accidental ingestion may cause gastrointestinal effects with irritation, nausea, vomiting, dizziness, coma and death. Aspiration into the lungs during ingestion or vomiting may cause lung damage.

#### HEALTH HAZARDS:

**INHALATION:** Excessive inhalation of vapors or mists may cause upper respiratory tract irritation and central nervous system effects including headache, nausea, dizziness, drowsiness, weakness, confusion, unconsciousness and coma.

**SKIN CONTACT:** May cause irritation. n-Hexane may be absorbed through the skin possibly resulting in symptoms similar to those listed under inhalation.

**EYE CONTACT:** May cause moderate irritation.

**INGESTION:** Unlikely due to aerosol container. Swallowing may cause gastrointestinal disturbances including abdominal pain, belching, nausea, vomiting, dizziness, drowsiness, visual disturbances, coma or death. May cause central nervous system depression with unsteady gait and sedation. Aspiration into the lungs may occur during ingestion or vomiting may cause lung damage. Kidney and liver damage may also occur.

**CHRONIC EFFECTS OF OVEREXPOSURE:** Long term inhalation exposure can cause visual disturbances, nausea, mental confusion, breathing difficulties and peripheral nerve damage with symptoms of numbness and tingling in the extremities. Prolonged or repeated contact with this product may possibly lead to irritation and dermatitis. Intentional misuse by deliberately concentrating and inhaling the product may be harmful or fatal.

**CARCINOGENICITY:** None of the components of this product are listed as a carcinogen or suspected carcinogen by IARC, NTP or OSHA.

### SECTION 3: HAZARDS IDENTIFICATION (continued)

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Individuals with chronic skin and nervous system disorders may be at increased risk from exposure to this material. Breathing of vapor and/or mist may aggravate respiratory disorders.

### SECTION 4 EMERGENCY and FIRST AID PROCEDURES

**EYE CONTACT:** Immediately flush eye with water for at least 15 minutes while lifting the upper and lower lids. Get medical attention.

**SKIN CONTACT:** Remove contaminated clothing immediately and launder before reuse. Wash thoroughly with soap and water. Get medical attention if irritation develops.

**INHALATION:** Remove victim to fresh air. If breathing has stopped give artificial respiration. If breathing is difficult have qualified personnel administer oxygen. Get medical attention.

**INGESTION:** Unlikely due to aerosol container. Do not induce vomiting. Rinse mouth out with water. Get immediate medical attention by calling a Poison Control Center or hospital emergency department.

### SECTION 5 FIRE and EXPLOSION HAZARD DATA

**FLASH POINT:** <15°F/-9°C

**METHOD:** TCC

**FLAMMABLE LIMITS:** (vol % in air) LEL: 1.1% (hexane)

UEL: 7.5% (hexane)

**AUTOIGNITION TEMPERATURE:** Not established

**AEROSOL PROTECTION LEVEL (NFPA 30B):** Level 1

**EXTINGUISHING MEDIA:** Water fog, foam, dry chemical or carbon dioxide. Cool fire exposed containers with water.

**SPECIAL FIREFIGHTING PROCEDURES:** Firefighters should wear full emergency equipment and NIOSH approved positive pressure self-contained breathing apparatus. Use shielding to protect against bursting cans.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable aerosol. Contents under pressure. Keep away from heat and open flames. Containers may rupture or explode at temperatures above 120°F.

### SECTION 6 ACCIDENTAL RELEASE MEASURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Wear appropriate protective equipment. Remove all sources of ignition. Ventilate area. Collect material for disposal using non-combustible absorbent material and place in a container suitable for flammable waste.

### SECTION 7 HANDLING and STORAGE

Flammable Aerosol.

Avoid contact with eyes, skin and clothing. Avoid breathing vapors and mists. Use with adequate ventilation. Wash thoroughly after handling. Remove contaminated clothing and launder before re-use. No smoking in use or storage area.

Protect containers from physical damage. Store in a cool, well ventilated area at temperatures below 120°F. Store away from direct sunlight. Do not incinerate containers.

Empty containers retain product residues. Do not cut, weld, braze, etc. on or near empty containers. Follow all MSDS precautions in handling empty containers.

### SECTION 8 EXPOSURE CONTROLS and PERSONAL PROTECTION

**RESPIRATORY PROTECTION:** None needed under normal use conditions with adequate ventilation. If the TLV is exceeded use a NIOSH approved respirator with organic vapor cartridges and a particulate pre-filter (R or P series). For higher concentrations (greater than 10 times the TLV) a NIOSH approved supplied air respirator (with escape bottle if required) or self-contained breathing apparatus may be required. Selection of respiratory protection depends on the contaminant type, form and concentration. Select in accordance with OSHA 1910.134 and good Industrial Hygiene practice.

**VENTILATION:** Good general room ventilation (equivalent to outdoors) should be adequate under normal conditions. If the recommended exposure limit is exceeded increased, explosion-proof mechanical ventilation such as local exhaust may be required.

**GLOVES:** Nitrile rubber or other impervious gloves are recommended where prolonged or repeated skin contact is likely.

**EYE PROTECTION:** Safety glasses or goggles recommended.

**OTHER PROTECTIVE EQUIPMENT:** Impervious apron, boots and other clothing are recommended if needed to avoid prolonged/repeated skin contact. Suitable washing facilities should be available.

#### SECTION 9 PHYSICAL and CHEMICAL PROPERTIES

|  |  |
|--|--|
| <b>BOILING POINT (@ 760 mmHg):</b> 200°F                                   | <b>MELTING POINT:</b> Not available            |
| <b>SPECIFIC GRAVITY (H<sub>2</sub>O=1):</b> 0.69                           | <b>VOLATILE:</b> 32%                           |
| <b>VAPOR PRESSURE (@ 70°F mm Hg):</b> 100 psi                              | <b>(VAPOR DENSITY (AIR=1):</b> >1              |
| <b>EVAPORATION RATE (Butyl Acetate =1):</b> >1                             | <b>COEFFICIENT OF WATER/OIL:</b> Not available |
| <b>APPEARANCE AND ODOR:</b> Clear, colorless liquid, sweet petroleum odor. |  |

#### SECTION 10 STABILITY and REACTIVITY

**STABILITY:** This material is stable.

**CONDITIONS TO AVOID:** Avoid heat., sparks and open flames. Avoid exposure to temperatures above 120°F.

**INCOMPATIBILITY:** Strong oxidizing agents, acids and bases.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition may yield carbon monoxide and carbon dioxide.

**HAZARDOUS POLYMERIZATION:** Will not occur.

#### SECTION 11 TOXICOLOGICAL INFORMATION

|  |                                       |
|--|---------------------------------------|
| <b>ACUTE TOXICITY VALUES:</b> n-Hexane | LD50 Oral rat: 28,710 mg/kg           |
|  | LC50 Inhalation rat: 48,000 ppm/4 hr. |
| Polyisobutylene                        | No data available                     |
| Carbon Dioxide:                        | No data available                     |

None of the components is listed as a carcinogen or suspect carcinogen by NTP, IARC or OSHA.

n-Hexane have been positive in a mammal cell cytogenetic analysis.

None of the components are known to cause sensitization in animals or humans.

n-Hexane has been shown to cause embryofetal toxicity in laboratory animals.

#### SECTION 12: ECOLOGICAL INFORMATION

There is no ecotoxicity data available for this product at this time.

**SECTION 13: DISPOSAL INFORMATION**

**WASTE DISPOSAL METHOD:** This product is RCRA Hazardous Waste (Ignitable) if discarded in the purchased form. Dispose in accordance with federal, state and local regulations. Do not incinerate containers. Dispose in accordance with all local, state and federal regulations.

**SECTION 14: TRANSPORTATION INFORMATION**

**DOT SHIPPING DESCRIPTION :** Consumer Commodity, ORM-D

**DOT HAZARD CLASSIFICATION:** ORM-D

**DOT LABELS REQUIRED (49CFR172.101):** None

**UN NUMBER:** None

**SECTION 15: REGULATORY INFORMATION**

**OSHA HAZARD CLASSIFICATION:** Flammable, pressure hazard, irritant, toxic, target organ effects.

**EPA SARA 302:** This product does not contain chemicals regulated under SARA Section 302.

**EPA SARA 311 HAZARD CLASSIFICATION:** Acute health, chronic health, fire hazard, sudden pressure release.

**EPA SARA 313:** This product contains the following chemicals that are regulated under SARA Title III, section 313:

|          |          |        |
|----------|----------|--------|
| n-Hexane | 110-54-3 | 30-40% |
|----------|----------|--------|

**CERCLA Hazardous Substances (Section 103)/RQ:** Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for the product, based on the RQ for n-Hexane (40% maximum) of 5,000 lbs, is 12,500 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**WHMIS CLASSIFICATION:** Class B-5, Flammable Aerosol; Class D-2, Subdivision B: Toxic material causing other chronic effects.

**EU CLASSIFICATION:** Highly Flammable (F) , Harmful (Xn)

**EU RISK AND SAFETY PHRASES:** R11, R48/20, S2, S16, S43, S51

**TOXIC SUBSTANCES CONTROL ACT:** All of the components of this product are listed on the TSCA inventory.

**CALIFORNIA PROPOSITION 65:** This product is not known to contain any chemicals which are known to the State of California to cause cancer or reproductive harm.

**Canada:** All of the components of this product are listed on the Canadian Domestic Substances List (DSL).

**EEC EINECS:** All of the ingredients are listed on the EINECS inventory.

**Australia:** All of the ingredients of this product are listed on the Australian Inventory of Chemical Substances.

**SECTION 16: OTHER INFORMATION**

NFPA Rating: Health: 1 Fire: 3 Reactivity: 0